

Which one of the symbol is used to represent a decision in a flow chart ?

Answer (Please select your correct option)



correct

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306



Made By: Waqar Siddhu

In Flow Chart, flow of control is represented by _____.

Answer (Please select your correct option)

☐ Rectangle

☐ Circle

☐ Diamond

☐ Arrow

correct

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu

There can be _____ 'default' statement(s) in any switch structure .

Answer (Please select your correct option)

☐ 1

☐ 2

correct

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐ 3

☐ n

Made By: Waqar Siddhu

The condition in loop should be a(n) _____.

Answer (Please select your correct option)

☐ Constant Expression

☐ Boolean Expression

☐ Primary Expression

☐ Arithmetic Expression

correct

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043100

Made By: Waqar Siddhu

How many nested loops would be required to manipulate n-dimensional array?

Answer (Please select your correct option)

- ☐ n
- ☐ n + 1
- ☐ n - 1
- ☐ 2n

correct

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu

Which of the following is not an example of int data type?

Answer (Please select your correct option)

- ☐ 0
- ☐ -32
- ☐ 65531
- ☐ -4.0

correct

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu

We should use _____ for clarity and to force the order of evaluation in an expression.

Answer (Please select your correct option)

☐ Brackets []

☐ parenthesis ()

correct

☐ curly braces { }

☐ quotation marks " "

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu

Which of the following is the starting index of an array in C++?

Answer (Please select your correct option)

☐ 0

correct

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐ 1

☐ -1

☐ 2

Made By: Waqar Siddhu



The statement $x += y$ can be interpreted as _____.

Answer (Please select your correct option)

☐ Adding the value of the x to the value of the y and storing the result in x

correct

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐ Adding the value of the y to the value of the x, store the result in y

☐ Adding the value of the x to the value of the x, store the result in x

☐ Adding the value of the y to the value of the y, store the result in x

Made By: Waqar Siddhu

Given a 2D array of integers, what would be the correct way of assigning the value 5 to the element at second row and third coloum ?

Answer (Please select your correct option)

☐ `m[2][3] = 5 ;`

correct

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐ `m[3][2] = 5 ;`

☐ `m[1][2] = 5 ;`

☐ `m[2][3] = '5' ;`

Made By: Waqar Siddhu

Array is a data structure that stores_____.

Answer (Please select your correct option)

☐ Memory addresses

☐ Variables

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

correct

☐ Data type

☐ Data

Made By: Waqar Siddhu

A program statement that invokes a function is called _____.

Answer (Please select your correct option)

☐ function declaration

☐ function call

correct

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐ function definition

☐ function prototype

Made By: Waqar Siddhu



If a function has been declared but not defined before its function call then it is termed as _____.

Answer (Please select your correct option)

- ☐ logical error
- ☐ syntax error
- ☐ run time error
- ☐ program time error

Made By: Waqar Siddhu

The Compiler of C language is written in-----language.

Answer (Please select your correct option)

☐ JAVA

☐ BASIC

☐ FORTRON

☒ C

correct

Correct Answer Solved By Hadi
usmanraj20@gmail.com
0321-8442906

Made By: Waqar Siddhu

To convert the value of one type into another type using built-in functions, we include _____ header file.

Answer (Please select your correct option)

☐ conio.h

☐ stdlib.h

☐ iostream.h

☐ string.h

correct

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



Which one of the below functions is not included in ctype.h header file?

Answer (Please select your correct option)

☐ isdigit(int c)

☐ isxdigit(int c)

☐ tolower(int c)

☐ getdigit(int c)

Made By: Waqar Siddhu

Which function is used to locate the first occurrence of a character in any string ?

Answer (Please select your correct option)

☐ strchr()

☐ strstr()

☐ strtok()

☐ strlen()

correct

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu

The function write() takes _____ as parameter(s).

Answer (Please select your correct option)

- ☐ String of pointer type
- ☐ String of variable lengths, no. of bytes to be read and flags
- ☐ Pointer array of characters and a delimiter
- ☐ String and no. of bytes to be written

correct

Correct Answer Solved By Hadi
usmanraj20@gmail.com

Made By: Waqar Siddhu



_____ is the pointer which determines the position in a file from where the next read operation occurs.

Answer (Please select your correct option)

☐ put

☐ seek

☐ get

☐ tell

Made By: Waqar Siddhu



Given a two dimensional array of integers, what would be the correct way of assigning the value 6 to the element at third row and fourth column?

Answer (Please select your correct option)

☐ array[2][3]=6;

☐ array[3][4]=6;

correct

☐ array[2][4]=6;

☐ array[4][3]=6;

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu

Write the syntax for calling a string manipulation function which compares the first 5 characters of an array "name" with the string "asdf".

Answer (Please [click here](#) to Add Answer)



Made By: Waqar Siddhu

What will be the value of x after the execution of the following code segment?

```
int x=10;  
int y=30;  
int *xptr = &x;  
x = *xptr + 10;
```

Answer ([Please click here to Add Answer](#))



Made By: Waqar Siddhu

Assume that you write a program to read the data from a text file. You have two options to do it, either reading the data character by character or reading multiple lines of data at a time. Which option do you think is more better and Why ?

Answer ([Please click here to Add Answer](#))



Made By: Waqar Siddhu

Consider that an integer pointer `xptr` contains the memory address `0x22ff50`. Now if the statement `xptr +=4;` is executed, how many bytes the pointer `xptr` will jump in the memory and what will be the new address of the `xptr`?

Answer ([Please click here to Add Answer](#))



Made By: Waqar Siddhu

Write a program which takes a string from the user and searches it within another string "This is my Pakistan".

For example, if the user enters the string "my" then after search, the program should display the message "String found" otherwise it should display the message "string not found".

Answer ([Please click here to Add Answer](#))



Made By: Waqar Siddhu

Detect and correct compile time error(s) in the following code.

Hints: The following code print numbers from 1 to 100.

```
void main()  
{
```

Answer ([Please click here to Add Answer](#))




Made By: Waqar Siddhu

```
int counter;  
float *ptr;  
  
for ( counter =1; counter <= 100; counter++)  
{  
    ptr = counter;
```

Answer ([Please click here to Add Answer](#))**Made By: Waqar Siddhu**

```
cout << ptr << " ";  
  
getch();  
return 0;  
}
```

Answer ([Please click here to Add Answer](#))



Made By: Waqar Siddhu