Question # 1 of 10 (Start time: 08:43:07 PM) Total Marks: 1
Which function is used to create cancel button event of dialog box _____.
Select correct option:
 OnInitCancel()
 OnClickCancel()
 CancelClick()
 OnCancel()

Question # 2 of 10 (Start time: 08:44:25 PM) Total Marks: 1
Consider the following C# code segment: button.Background = (Brush) new
BrushConverter().ConvertFrom ("SystemColors.WindowBrush"); Which one of the following is
equivalent XAML code?
Select correct option:
 <Button Background= "SystemColors.WindowsBrush"/>
 <Button Background= "SystemColor.WindowsBrush"/>
 <Button Background= "SystemColor.WindowBrush"/>
 <Button Background= "SystemColors.WindowBrush"/>

Question # 3 of 10 (Start time: 08:45:51 PM) Total Marks: 1
Multi touch events are categorized into _____ and _____.
Select correct option:
 Touch events, touchup events
 Touchdown events, touchup events
 Advanced touch events, low-level manipulation events
 Basic touch events, higher-level manipulation events

Question # 4 of 10 (Start time: 08:46:26 PM) Total Marks: 1
Which of the following components generates an input Event?
Select correct option:
 Printer
 Multi Touch
 Plotter
 Speaker

Question # 5 of 10 (Start time: 08:47:00 PM) Total Marks: 1
Using _____ requires more overhead than _____ because of the extra tracking.
Select correct option:
 StaticResource, DynamicResource
 DynamicResource, StaticResource
 PermanentResource, TemporaryResource
 TemporaryResource, PermanentResource

Question # 6 of 10 (Start time: 08:47:56 PM) Total Marks: 1
We use "UIElement" property ClipToBounds= "false" when _____.
Select correct option:
 We want area child element don't cross the boundary of parent
 None of given
 We want area of child element is allowed to cross the boundary of parent
 Parent area also increases on increasing of area of child element

Question # 7 of 10 (Start time: 08:49:22 PM) Total Marks: 1
The Java programming language has a specific class for creating splash screens, called _____.
Select correct option:
Java.awt.start
Java.lang.splash
Java.start.screen
Java.awt.SplashScreen

Question # 8 of 10 (Start time: 08:50:33 PM) Total Marks: 1
_____ is used to perform navigation.
Select correct option:
Session
Hyperlink
Hypertext markup language code
Internet protocol

Question # 9 of 10 (Start time: 08:51:28 PM) Total Marks: 1
Which of the following operation cannot be performed by using a View?
Select correct option:
Grouping
Filtering
Sorting
Searching

Question # 10 of 10 (Start time: 08:52:36 PM) Total Marks: 1
To design a complex Interface, which of the following technique is best to achieve the required results?
Select correct option:
Panels composed in three panels
Panels composed within panels
Panels composed in two panels
Panels composed in single panel

Question # 1 of 10 (Start time: 08:18:20 PM) Total Marks: 1
Which of the following is not a string format property throughout WPF?
Select correct option:
ContentStringFormat
ItemStringFormat
RowHeaderStringFormat
StringFormat

Question # 2 of 10 (Start time: 08:19:31 PM) Total Marks: 1
In multi touch events, a/an _____ id is assigned to each individual event.
Select correct option:
Device
Processor
CPU
Event

Question # 3 of 10 (Start time: 08:20:03 PM) Total Marks: 1
Commonly we have two types of custom command bindings named as _____.
Select correct option:
 StartBindings and StopBindings
 EventBindings and InstanceBindings
 ButtonBindings and TextboxBindings
 <mark>KeyBindings and MouseBindings</mark>

Question # 4 of 10 (Start time: 08:21:16 PM) Total Marks: 1
Which of the following is an example of tunnel key event?
Select correct option:
 Key up
 Preview key entered
 <mark>Preview key down</mark>
 Key down

Question # 5 of 10 (Start time: 08:22:32 PM) Total Marks: 1
In context of data binding, _____ contains the current item to get it synchronized with data
source.
Select correct option:
 String
 Template
 View
 <mark>List</mark>

Question # 6 of 10 (Start time: 08:24:12 PM) Total Marks: 1
Multi touch events are categorized into _____ and _____.
Select correct option:
 Touch events, touchup events
 Touchdown events, touchup events
 Advanced touch events, low-level manipulation events
 <mark>Basic touch events, higher-level manipulation events</mark>

Question # 7 of 10 (Start time: 08:25:34 PM) Total Marks: 1
Which function is used to create cancel button event of dialog box _____.
Select correct option:
 OnInitCancel()
 <mark>OnClickCancel()</mark>
 CancelClick()
 OnCancel()

Question # 8 of 10 (Start time: 08:26:59 PM) Total Marks: 1
_____and _____ are the two important properties of Binding object.
Select correct option:
 Start, Destination
 Items, Selected
 <mark>Source, Path</mark>
 BindTo, BindFrom

Question # 9 of 10 (Start time: 08:28:29 PM) Total Marks: 1
Which one of the following panels is most powerful, versatile and customizable?
Select correct option:
 Grid Panel
 Canvas panel
 Doc panel
 Stack panel

Question # 10 of 10 (Start time: 08:29:03 PM) Total Marks: 1
An event that is raised whenever the value of "CanExecute" changes is known as _____.
Select correct option:
 CanExecute
 CanExecuteChanged
 Command
 Execute

Question # 10 of 10 (Start time: 09:46:15 PM) Total Marks: 1
In order to resize the row and column in Grid panel, _____ is used.
Select correct option:
 Grid divider
 Grid compiler
 Grid converter
 Grid splitter

Which of the following is an example of tunnel key event?
Select correct option:
 Key up
 Preview key entered
 Preview key down
 Key down

Question # 2 of 10 (Start time: 09:04:53 PM) Total Marks: 1
Data binding is about tying together arbitrary .NET _____.
Select correct option:
 Objects
 Functions
 Properties
 Variables

Question # 5 of 10 (Start time: 09:06:36 PM) Total Marks: 1
_____ supports the creation of applications that run directly in a web browser.
Select correct option:
 WPF
 C/C++
 C#
 HTML

Question # 6 of 10 (Start time: 09:07:13 PM) Total Marks: 1
Which of the following operation cannot be performed by using a View?
Select correct option:

Grouping

Filtering

Sorting

<mark>Searching</mark>

Question # 7 of 10 (Start time: 09:07:41 PM) Total Marks: 1
_____ is used to perform navigation.
Select correct option:

Session

<mark>Hyperlink</mark>

Hypertext markup language code

Internet protocol

In context of data binding, _____ contains the current item to get it synchronized with data source.
Select correct option:

String

Template

View

<mark>List</mark>

_____ and _____ are the two important properties of Binding object.
Select correct option:

Start, Destination

Items, Selected

<mark>Source, Path</mark>

BindTo, BindFrom

Question # 8 of 10 (Start time: 09:08:10 PM) Total Marks: 1
To check that the user either pressed left Alt key or right Alt key, the _____ is used.
Select correct option:

<mark>IsKeyDown</mark>

IsDown

keyboardDevice.IsKeyDown

KeyStates.IsKeyDown

Question # 10 of 10 (Start time: 09:11:06 PM) Total Marks: 1
In _____ browser app, you change "<TargetZone>Internet</TargetZone>" to
"<TargetZone>Custom</TargetZone>"
Select correct option:

Partial-trust

Full-reject

Partial-reject

<mark>Full-trust</mark>

Question # 1 of 10 (Start time: 09:13:52 PM) Total Marks: 1
_____ provides the logic behind the "Back" and "Forward" buttons.
Select correct option:
 Hyperlink
 Navigation Window
 IFrame
 <mark>Journal</mark>

Question # 7 of 10 (Start time: 10:08:33 PM) Total Marks: 1
In multi touch events, when multiple fingers are touching simultaneously, these events get raised for each finger _____.
Select correct option:

 <mark>Independently</mark>
 Completely
 Partially
 Dependently

Question # 9 of 10 (Start time: 10:09:30 PM) Total Marks: 1
In a code segment, if the Visibility="Collapsed" then which of the following events are not generated?
Select correct option:
 Key down Events
 <mark>Mouse Events</mark>
 Routed Events
 Keyboard Events

Question # 7 of 10 (Start time: 10:17:09 PM) Total Marks: 1
A Window can spawn _____ number of additional Windows by instantiating a Window-derived class and calling Show(...).
Select correct option:
 Four

 <mark>Any</mark>
 Six
 Five

Question # 3 of 10 (Start time: 10:22:29 PM) Total Marks: 1
Frame has a _____ property used in enabling or disabling the bar.
Select correct option:
 ShowsNavigationUI
 BlocknavigationUI
 <mark>NavigationUIVisibility</mark>
 NavigationUIBlock

Question # 4 of 10 (Start time: 10:23:10 PM) Total Marks: 1
If we insert some objects in a single cell in Grid panel, then these objects are placed on _____
Select correct option:
 <mark>One on Top of the other</mark>
 One after the other
 One on Bottom of the other

One on Side of the other

Question # 6 of 10 (Start time: 10:24:01 PM) Total Marks: 1
A _____ receives keyboard events only if it has keyboard focus.
Select correct option:
 Mouse
 Keyboard Controls
 Keyboard
 UIElement

Question # 1 of 10 (Start time: 09:53:44 PM) Total Marks: 1
To remove data binding between the source and the target, we can use _____ function.
Select correct option:
 ClearBinding
 ResetBinding
 StopBinding
 RemoveBinding

Question # 2 of 10 (Start time: 09:54:31 PM) Total Marks: 1
A/An _____ screen is an image that appears while a game or program is loading
Select correct option:
 Opening
 Initial
 Splash
 Startup

Question # 3 of 10 (Start time: 09:54:52 PM) Total Marks: 1
We can perform sorting through View by using an object of _____ class.
Select correct option:
 ViewOrder
 ViewDescription
 SortOrder
 SortDescription

Question # 4 of 10 (Start time: 09:55:44 PM) Total Marks: 1
"Binding" technique binds two properties together and keeps a _____ open.
Select correct option:
 Memory location
 Selection
 Choice
 Communication channel

Which one of the following can be used to set dependency property values?
Select correct option:
 Temporary resource
 Permanent resource
 Dynamic resource
 Static resource

Question # 6 of 10 (Start time: 09:56:53 PM) Total Marks: 1
_____ is used to perform navigation.
Select correct option:
 Session
 Hyperlink
 Hypertext markup language code
 Internet protocol

Question # 7 of 10 (Start time: 09:57:13 PM) Total Marks: 1
Which one of the following is used, if we want to add a window resource in procedural code?
Select correct option:
 Window.Resource.Add ();
 <Widows.Resources></Widows.Resources>
 Window.Resoruces.Add();
 <Window.Resources></Window.Resources>

Question # 8 of 10 (Start time: 09:57:49 PM) Total Marks: 1
We use "GetDefaultView" method of _____ to get the default View.
Select correct option:
 CollectionViewSource
 DataSource
 ViewDescription
 ViewCollection

Question # 8 of 10 (Start time: 09:57:49 PM) Total Marks: 1
We use "GetDefaultView" method of _____ to get the default View.
Select correct option:
 CollectionViewSource
 DataSource
 ViewDescription
 ViewCollection

Question # 9 of 10 (Start time: 09:58:54 PM) Total Marks: 1
In case of HTML page navigation, you must use the _____ of "Navigate" that _____ a URI.
Select correct option:
 Overload, rejects
 IFrame, rejects
 IFrame, accepts
 Overload, accepts

Question # 10 of 10 (Start time: 10:00:08 PM) Total Marks: 1
The Java programming language has a specific class for creating splash screens, called _____.
Select correct option:
 Java.awt.start
 Java.lang.splash
 Java.start.screen
 Java.awt.SplashScreen

In case of integrating Navigation to XBAP, "ShowNavigationUI" should be set to _____ in order to bypass integration.
Select correct option:

False

True

Null

0